




[N-Type]

182 Mono-Bifacial Module
GPM10TG-585(144)

580W-605W



Maximum output power
585W

Maximum efficiency
22.63%

Power tolerance
0~+3%

► Key Features



SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



Hot 2.0 Technology

The N-type module with Hot 2.0 technology has better reliability and lower LID/LETID.




PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



Duplex power generation

The power gain on both sides increases with the light received on the back, up to 25%.



Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).

► Quality System

IEC 61215-1:2021, IEC 61730-1:2023

IEC61701 / IEC62716 / IEC62804

ISO9001:2015:Quality Management System

ISO14001:2015:Environment Management System

ISO45001:2018:Occupational Health and Safety Management Systems

► Product Certifications




► Linear performance warranty


15Year Product Warranty

30Year Linear Warranty


0.4%Annual Degradation Over **30** Years



Engineering Drawings



Electical Performance(585W)



Electrical Parameters (STC*)

Maximum Power(W)	580	585	590	595	600	605
Maximum Power Voltage(V)	44.02	44.22	44.43	44.64	44.85	45.06
Maximum Power Current(A)	13.18	13.23	13.28	13.33	13.38	13.43
Open Circuit Voltage(V)	51.95	52.16	52.37	52.58	52.79	53.00
Short Circuit Current(A)	14.00	14.04	14.08	14.12	14.16	14.20
Module Efficiency(%)	22.45	22.65	22.84	23.03	23.23	23.42

Power tolerance 0~+3%

Bifaciality 80%±5%

*Irradiance 1000W/m², Module Temperature 25°C, Air Mass 1.5

Mechanical Parameters

Cell Type	182×91mm N-Type
Number of Cells	144cells (2x72)
Dimensions	2278×1134×30mm
Weight	31.8KG
Front Glass	2.0mm, Anti-Reflection Coating
Back Glass	2.0mm, Heat Strengthened Glass
Frame	composite frame/steel frame/anodized aluminium alloy frame
J-Box	IP68 Rated, MC4 Compatible
Output cable	4 mm², 300 mm standard

Electrical Parameters (NOCT*)

Maximum Power(W)	432.1	435.8	439.6	443.3	447.0	450.7
Maximum Power Voltage(V)	40.74	40.92	41.12	41.31	41.51	41.70
Maximum Power Current(A)	10.61	10.65	10.69	10.73	10.77	10.81
Open Circuit Voltage(V)	48.08	48.27	48.47	48.66	48.86	49.05
Short Circuit Current(A)	11.27	11.30	11.33	11.37	11.40	11.43

* Irradiance 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s

Temperature Coefficient

Nominal Operating Cell Temperature (NOCT)	45±2°C
Temperature Coefficient of Isc	0.045%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Pmax	-0.29%/°C

Backside Power Gain (For 585W)

Backside Power Gain(%)	10%	15%	20%	25%	30%
Maximum Power(Pmax/W)	643.5	672.8	702.0	731.3	760.5
Open Circuit Voltage(Voc/V)	52.36	52.36	52.86	52.86	52.86
Short Circuit Current(Isc/A)	15.39	16.06	16.57	17.23	17.90
Maximum Power Voltage(Vmp/V)	44.42	44.42	44.92	44.92	44.92
Maximum Power Current(Impp/A)	14.49	15.15	15.63	16.28	16.93

Application Parameters

Operational Temperature(°C)	-40°C~+85°C
Maximum System Voltage	1500V DC
Max Series Fuse Rating	25A
Wind/ Snow Load	2400Pa/5400Pa
Packaging Configuration	37PCS/PLT,740PCS/40HQ

