

HOSUN



DUAL GLASS

BACK CONTACT
SOLAR MODULE

HO-Max

655 – 690W

HOSUN-A-GRH66DW

Full-Screen

15
YEARS

Product Warranty

30
YEARS

Performance Guarantee



Partial Shading
Optimisation



Better Temperature
Coefficient



High Temperature
Restriction



Micro-crack
Resistance



Higher Power



Lower BOS



More Aesthetic
Values



Full Screen
Technology



690W

Power Output Up To

25.5%

Maximum Efficiency



30 Years

Performance Guarantee

Electrical Characteristics (STC: AM1.5 1000W/m² 25°C NOCT: AM1.5 800W/m² 20°C 1m/s Power Tolerance:0~+3%)

Module Type	HOSUN-A655 -GRH66Dw		HOSUN-A660 -GRH66Dw		HOSUN-A665 -GRH66Dw		HOSUN-A670 -GRH66Dw		HOSUN-A675 -GRH66Dw		HOSUN-A680 -GRH66Dw		HOSUN-A685 -GRH66Dw		HOSUN-A690 -GRH66Dw	
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
P _{max} [W]	655	499	660	503	665	507	670	511	675	514	680	518	685	522	690	525
V _{oc} [V]	49.80	47.62	49.90	47.72	50.00	47.82	50.10	47.91	50.20	48.01	50.30	48.10	50.40	48.20	50.50	48.29
V _{mp} [V]	40.80	39.08	40.90	39.18	41.00	39.27	41.11	39.37	41.21	39.46	41.32	39.56	41.43	39.65	41.53	39.75
I _{sc} [A]	16.72	13.48	16.80	13.54	16.88	13.60	16.96	13.66	17.04	13.71	17.12	13.77	17.20	13.82	17.28	13.88
I _{mp} [A]	16.06	12.76	16.14	12.83	16.22	12.90	16.30	12.97	16.38	13.03	16.46	13.09	16.54	13.16	16.62	13.22
Module Efficiency	24.2%		24.4%		24.6%		24.8%		25.0%		25.2%		25.4%		25.5%	

30-year Linear Performance Curve



STRUCTURAL CHARACTERISTICS

Dimension (L*W*H)	2382*1134*30mm
Weight (kg)	32.5kg ± 3%
Cell type	N-Type HSBC
Bifacial Factor	80 ± 5%
No. of Cells	132(6*22)
Glass	Dual glass, 2.0+2.0mm coated semi tempered glass
Frame	Anodized aluminum
Cable	4mm ² (IEC) 12AWG(UL) +400mm, -200mm or Customized Length
Junction Box	IP68, 3 bypass diodes
Connector	MC4 Compatible / Original MC4-EVO2A
Package Detail	36 pcs per pallet / 144 pcs per 20'GP / 720 pcs per 40'HC

Temperature Ratings (STC)

Temperature Coefficient of I _{sc}	+ 0.05% / °C
Temperature Coefficient of V _{oc}	- 0.22% / °C
Temperature Coefficient of P _{max}	- 0.26% / °C

Installation Guide

Operation Temperature	-40°C - +70°C
Maximum Series Fuse Rating	30A
Protection Class	Class II
Maximum System Voltage	DC1500V
Maximum Static Loading	+5400Pa / -2400Pa
Hail Test	25 mm diameter hail at 23 m/s
Fire Rating	IEC Class A

Contact us: info@hosunenergy.com



www.Korean-Solar.com
www.HosunEnergy.com

HOSUN-A-GRH66Dw Full-Screen

Ver.20260622EN

Technical and financial parameters in this datasheet may vary by region. HOSUN warrants not for their absolute accuracy. We reserve the right to amend any info herein without prior notice, due to our ongoing innovation & product improvement efforts. Clients are strongly advised to obtain the latest edition of this datasheet and integrate it as an integral part of the legally binding agreement signed by both parties.